

PCT


WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : C07C 17/383, 19/08, 19/10	A1	(11) International Publication Number: WO 99/50208 (43) International Publication Date: 7 October 1999 (07.10.99)
(21) International Application Number: PCT/US99/05917 (22) International Filing Date: 19 March 1999 (19.03.99) (30) Priority Data: 09/052,757 31 March 1998 (31.03.98) US (71) Applicant: ALLIEDSIGNAL INC. [US/US]; 101 Columbia Road, P.O. Box 2245, Morristown, NJ 07962-2245 (US). (72) Inventors: SWAIN, Charles, Francis; 4525 East Overlook Drive, Williamsville, NY 14221 (US). SINGH, Rajiv, Ratna; 18 Foxfire Drive, Getzville, NY 14068 (US). PHAM, Hang, Thanh; 96 Sunridge Drive, Amherst, NY 14229 (US). (74) Agents: CRISS, Roger, H. et al.; AlliedSignal Inc., Law Dept. (Amy Olinger), 101 Columbia Road, P.O. Box 2245, Morristown, NJ 07962-2245 (US).		(81) Designated States: JP, KR, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i>

(54) Title: PURIFICATION OF HYDROFLUOROCARBONS



(57) Abstract

A process for the purification of difluoromethane comprising: (a) subjecting a mixture comprising at least difluoromethane (HFC-32) and dichlorodifluoromethane (CFC-12) to a first distillation step in which a majority of either CFC-12 or HFC-32 is concentrated in a first distillate and a majority of the other component is concentrated in first bottoms; and (b) subjecting the first distillate in step (a) to at least one additional second distillation step conducted at a different pressure in which a majority of the component concentrated in said first distillate is concentrated in second bottoms and in which the other component is concentrated in a second distillate; and (c) recovering purified HFC-32 from one of said first or second bottoms.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

PURIFICATION OF HYDROFLUOROCARBONS

FIELD OF INVENTION

5 The present invention relates broadly to the purification of hydrofluorocarbons. More specifically, the present invention relates to the separation of an azeotrope of dichloromethane (HFC-32) and dichlorodifluoromethane (CFC-12).

BACKGROUND OF THE INVENTION

10 Difluoromethane (HFC-32) is a hydrofluorocarbon developed to replace ozone-depleting hydrochlorofluorocarbons (HCFCs) or chlorofluorocarbons (CFCs) refrigerants/refrigerant blends. During the production of HFC-32, certain by-products are formed, including CFC-12, which is of particular interest herein. It has been found that CFC-12 and HFC-32 form a low-boiling azeotrope in the
15 distillation of HFC-32.

Such an azeotropic cannot be separated using conventional distillation techniques. Furthermore, alternative methods of separating CFC-12 from HFC-32 such as extraction, extractive distillation, or absorption introduce higher costs and additional components to the purification process.

20 Although further recovery of HFC-32 tends to be difficult, it is nevertheless necessary to maintain high yields. For example, if no additional recovery of HFC-32 is performed on an azeotropic distillate containing about 9.2 wt % CFC-12 (as would be obtained through economical, high pressure distillation), then an HFC-32 yield loss of at least 10% can be expected. In other
25 words, without further recovery, the HFC-32 yield would be less than 90%.

Therefore, a need exists for a process which recovers HFC-32 in high yield from the CFC-12/HFC-32 azeotropic distillate, but which does not involve costly

and complex distillation techniques and apparatus. The present invention fulfills this need among others.

DESCRIPTION OF THE INVENTION AND PREFERRED EMBODIMENTS

5 The present invention provides for high yield recovery of HFC-32 from a mixture containing CFC-12 using swing distillation in which the mixture is distilled at various pressures to effect separation. Distilling the mixture at different pressures effects separation because it has been found that the composition of the HFC-32/CFC-12 azeotrope changes *significantly* upon a change
10 in pressure. Although some change in an azeotrope's composition can be expected with a change in pressure, it has been found that the composition of the HFC-32/CFC-12 azeotrope changes approximately 20 wt % from atmospheric pressure to about 200 psia. This is more than one skilled in the art would expect.

15 Such a significant composition differential facilitates separation because either HFC-32 or CFC-12 will tend to concentrate in the distillate during distillation at one pressure, and then, upon distillation of the distillate at a different pressure, will tend to concentrate in the bottoms. This way, the component can be removed from the mixture through the bottoms.

20 Additionally, since these pressures are within the operating parameters of conventional distillation equipment, the process of the present invention can be practiced using existing equipment with little or no modification.

25 One aspect of the present invention is a process for the purification of HFC-32 from a mixture of HFC-32/CFC-12. The process comprises: (a) subjecting a mixture comprising at least HFC-32 and CFC-12 to a first distillation step in which a majority of either CFC-12 or HFC-32 is concentrated in a first distillate and a majority of the other component is concentrated in a first bottoms; and (b) subjecting the first distillate in step (a) to at least one additional distillation step conducted at a different pressure in which a majority of the component concentrated in said first distillate is concentrated in a second bottoms and in

which the other component is concentrated in a second distillate; (c) optionally recycling said second distillate to said first distillation step at least once; and (d) recovering purified HFC-32 from one of said first or second bottoms.

5 Another aspect of the present invention is a process for further recovering HFC-32 from an azeotropic distillate comprising HFC-32/CFC-12 as obtained from the distillation of HFC-32 by subjecting the azeotrope distillate to pressure swing distillation to recover HFC-32 in yields of no less than about 90%.

10 The process of the present invention may be performed using batch distillation or continuous distillation. In large scale commercial production, continuous distillation is preferred. A preferred continuous distillation system is shown schematically in Figure 1. Feed material (F) containing less than the low pressure azeotropic concentration of CFC-12 is fed into the first distillation column (C-1) and operated at low temperature, preferably close to atmospheric pressure. At such low pressures, the azeotrope is relatively high in CFC-12
15 concentration. Consequently, the overhead distillate (1) from the low pressure distillation column (C-1) is greatly enriched with CFC-12. Bottom product (2) from the first low pressure distillation column (C-1) contains HFC-32 product with very low CFC-12 concentration.

20 The overhead distillate (1) from the first distillation column (C-1) is fed into a second distillation column (C-2) operating at a relatively high pressure. At such a high pressure, the amount of CFC-12 in the azeotrope drops dramatically. Consequently, distillate (3) contains a relatively high concentration of HFC-32, while, the bottoms (4) contains a relatively high concentration of CFC-12.

25 Optionally, distillate (3) from the second high pressure distillation column (C-2) is recycled to the first distillation column (C-1) to recover HFC-32 for high yield.

30 One skilled in the art will appreciate that modifications to the above system are possible. For example, the first distillation column (C-1) may be operated at a relatively high pressure, and distillate therefrom distilled at relatively low pressure in the second distillation column (C-2). Optionally, as above, the distillate from

the second distillation column (C-2) may be recycled to the first distillation column (C-1). This configuration may be preferred for feed compositions having a concentration of CFC-12 at or above CFC-12 azeotropic concentration as discussed below.

5 The precise configuration of whether the feed is first introduced into the high or low pressure column depends upon the feed composition and the process economics. As a general rule, feed composition must contain less than the azeotropic amount of CFC-12 at a particular pressure to remove a majority of the CFC-12 as distillate. If the CFC-12 concentration in the feed is the same or
10 greater than the azeotrope composition at the pressure of the low pressure column, then it must be fed into the high pressure column so that the majority of the CFC-12 can be removed efficiently as bottoms from the high pressure column. For example, if the low pressure distillation is conducted at atmospheric pressure, which corresponds to a CFC-12 azeotropic concentration of 29 wt %, then feeds
15 having a CFC-12 concentration below 29 wt % should be introduced in the low pressure distillation. However, any feed having a composition at or above 29 wt % CFC-12 should be fed to the high pressure distillation. One skilled in the art can readily determine the CFC-12 azeotropic concentrations for the low pressure distillation and compare this value to feed composition to determine whether the
20 feed should be introduced into the low or high pressure distillation step.

 Rather than performing the process of the present invention using continuous distillation, it may be preferable in certain circumstances, for example, in pilot plants, to perform the process using batch distillation. In batch distillation typically a single distillation column is used. The mixture may be fed, for
25 example, into a distillation column operating at high pressure. The distillate is then collected and refed into the column after it has been cleaned. This time, the column is operated at a low pressure. The purified HFC-32 is then recovered from the bottoms of the still operating at low pressure.

 Whether the distillation process is continuous or batch, the pressure at
30 which the distillations are conducted preferably are such that conventional distillation apparatus can be used. To this end, the low pressure distillation is

conducted at a pressure preferably no greater than about 40 psia, more preferably between about 5 and about 30 psia, and most preferably at about atmospheric pressure. The high pressure distillation is conducted at a pressure preferably between about 50 and about 400 psia, more preferably between about 100 and about 300 psia, and most preferably between about 175 and about 225 psia.

The temperatures at which these distillations are performed are directly related to the boiling points at the pressures used, and are well within the scope of knowledge of one skilled in the art.

The yields of HFC-32 from the azeotropic mixture using the process of the present invention far exceed those for conventional distillation. In a preferred embodiment, the yield of HFC-32 from the azeotropic mixture is no less than about 90%, more preferably no less than about 95% and even more preferably no less than about 99%.

Additionally, by using pressures and temperatures in this range, conventional equipment can be used in the above-mentioned process with little or no modification.

The following examples are illustrative of the practice of the present invention.

EXAMPLES

Example 1

This example shows the change in the composition of the CFC-12/HFC-32 with a change in pressure.

The system comprised a distillation unit comprising a two gallon stainless steel reboiler equipped with a SS-316 horizontal (U) two bundle heating coils.

Directly mounted to the reboiler was a 2" diameter by 100" packed distillation column containing 1/4" protruded metal distillation packing. A vertical shell and tube heat exchanger were mounted on the distillation column and cooled with circular cold methanol from a refrigeration unit. Vapor product from the partial condenser was condensed in a cylinder immersed in dry ice.

To this system crude HFC-32 reaction product containing 0.5 wt. % CFC-12 was added. The column was operated at 14.3 psia at an overhead temperature of -54°C. Distillate collected had a composition of 29 wt. % CFC-12.

In a same distillation column, the reboiler was again charged with crude HFC-32 containing 0.5% CFC-12. In this case, the distillation column was operated at 214 psia at a resultant overhead temperature of 12°C. Distillate collected had a composition of 9.2 wt. % CFC-12. The bottoms product contained 136ppm CFC-12.

Therefore, a drop in concentration of CFC-12 of almost 20 wt % was observed as the pressure increased from atmospheric to 214 psia.

Example 2

This example illustrates the process of the present invention using a single distillation column wherein the feed is introduced into the low pressure distillation.

A crude HFC-32 product stream containing 0.5 wt % CFC-12 obtained by the fluorination of methylene chloride with anhydrous hydrogen fluoride in the presence of a fluorination catalyst is charged to a distillation column.

The distillation column consists of an Inconel reboiler attached to a 2 inch diameter stainless steel column filled with 1/4" protruded ribbon packing made of Monel. A stainless steel condenser is mounted on top of the column. Chilled methanol is pumped to the condenser to provide cooling.

The distillation column is operated at about 14.3 psia, a reflux temperature of about -54°C and a reboiler temperature of about -50°C. Upon distillation, a distillate containing about 29 wt % CFC-12 is removed at a reflux ratio of about 10:1 until the reboiler CFC-12 content is reduced to about 0.05 wt %.

5 The distillate is then fed back into the column and distilled again. This time, the pressure in the distillation column is raised to about 214 psia by heating the reboiler using steam and raising the condenser temperature. The reflux and distillate from this second distillation is about 12°C. The distillate from this second distillation has a HFC-32/CFC-12 weight ratio of about 10:1.

10

Example 3

This example illustrates the process of the present invention using a single distillation column wherein the feed is introduced into the high pressure distillation.

15 A crude HFC-32 product stream containing 30 wt % CFC-12 obtained by the fluorination of methylene chloride with anhydrous hydrogen fluoride in the presence of a fluorination catalyst is charged to a distillation column.

20 The distillation column consists of an Inconel reboiler attached to a 2 inch diameter stainless steel column filled with ¼" protruded ribbon packing made of Monel. A stainless steel condenser is mounted on top of the column. Chilled methanol is pumped to the condenser to provide cooling.

25 The distillation column is operated at about 215 psia, a reflux temperature of about 12°C and a reboiler temperature of about 16°C. Upon distillation, a distillate containing about 9.2 wt % CFC-115 is removed at a reflux ratio of about 10:1 until the reboiler CFC-12 content is reduced to about 1 wt %.

The distillate is then fed back into the column and distilled again. This time, the pressure in the distillation column is decreased to about 14.3 psia by lowering the heat flow in the reboiler and decreasing the condenser temperature.

The reflux and distillate temperatures from this second distillation are about -54°C. The distillate from this second distillation has a HFC-32/CFC-12 weight ratio of about 2.4:1.

5 Therefore, using the process of the present invention, HFC-32 can be recovered with high yields.

Example 4

The following Example demonstrates the process using a system of multiple distillation columns as shown schematically in Fig. 1.

10 Crude HFC-32 product stream containing 0.5 wt % CFC-12 obtained by the fluorination of methylene chloride with anhydrous hydrogen fluoride in the presence of a fluorination catalyst is subjected to high pressure (200 psia) distillation (not shown in Fig. 1). This results in a HFC-32/CFC-12 azeotropic distillate containing 9.2 wt % CFC-12.

15 To a distillation column (C1), similar in structure to the distillation column of Example 2, is fed the azeotropic distillate. The distillation is conducted at 14.3 psia, a reflux temperature of about -54°C and a reboiler temperature of about -45°C. At such low pressures, the azeotrope is relatively high in CFC-12 concentration. Consequently, the distillate (1) contains a relatively high
20 concentration of CFC-12 (29 wt %). On the other hand, little CFC-12 is left in the bottom, and essentially pure HFC-32 (99.9 wt %) is removed as the bottom (2).

The distillate is then passed to a second distillation column (C2) similar in structure to (C1). The distillation is conducted at 214 psia, a reflux temperature
25 of about 12°C and a reboiler temperature of about 16°C. At such a high pressure, the amount of CFC-12 in the azeotrope drops dramatically. The azeotrope, now rich in HFC-32, is removed in distillate (3) and is refeed to distillation column (C1) for further recovery of HFC-32, while essentially pure CFC-12 (99.8 wt %) is removed as the bottoms (4).

Therefore, using the process of the present invention, HFC-32 can be recovered with high yields.

Example 5

5 This example illustrate the process of the present invention using more than two distillation columns.

Crude HFC-32 containing 0.5 wt % CFC-12 obtained by the fluorination of methylene chloride with anhydrous hydrogen fluoride in the presence of a fluorination catalyst is fed into a distillation column.

10 The distillation column consists of an Inconel reboiler attached to a 2 inch diameter stainless steel column filled with ¼" protruded ribbon packing made of Monel. A stainless steel condenser is mounted on top of the column. Chilled methanol is pumped to the condenser to provide cooling.

15 The distillation is conducted at about 14.3 psia, a reflux temperature of about -54°C and a reboiler temperature of about -50°C. The distillate is enriched in CFC-12 (29 wt %) while the bottom contains essentially pure HFC-32 (>99.9 wt %).

20 The distillate is then passed to a second distillation column similar to the first column in structure but operated at high pressure (i.e., about 214 psia), a reflux temperature of about 12°C. and a reboiler temperature of about 16°C. At this pressure, the distillate is enriched in HFC-32 (>91 wt %) while the bottoms contain more CFC-12 (>10 wt %).

25 The distillate is then fed to a third distillation column similar in structure to the first column and operated at low pressure (i.e., about 14.3 psia), a reflux temperature of about -54°C and a reboiler temperature of about -50°C. At this pressure, the distillate is becoming enriched in CFC-12 (about 29 wt %) while the bottoms are richer in HFC-32 (>99.9 wt %).

Finally, the distillate from this third distillation is fed to a fourth distillation column similar in structure to the first column but operated at about 214 psia, a reflux temperature of about 12°C, and a reboiler temperature of about 16°C. Under these conditions, HFC-32 (91 wt %) is recovered as distillate while the
5 bottoms are enriched in CFC-12 (> 90 wt %).

Therefore, using the process of the present invention, HFC-32 can be recovered with high yields.

CLAIMS

WHAT IS CLAIMED IS

1. A process for the purification of difluoromethane comprising:
 - (a) subjecting a mixture comprising at least difluoromethane (HFC-32) and dichlorodifluoromethane (CFC-12) to a first distillation step in which a majority of either CFC-12 or HFC-32 is concentrated in a first distillate and a majority of the other component is concentrated in a first bottoms; and
 - (b) subjecting the first distillate in step (a) to at least one additional second distillation step conducted at a different pressure in which a majority of the component concentrated in said first distillate is concentrated in a second bottoms and in which the other component is concentrated in a second distillate; and
 - (c) recovering purified HFC-32 from one of said first or second bottoms.
2. The process of claim 1, wherein steps (a) and (b) are repeated one or more times.
3. The process of claim 1, further comprising:
 - (c) recycling said second distillate to said first distillation step at least once.
4. The process of claim 1 wherein said distillation steps are conducted in a single column.
5. The process of claim 1 wherein said distillation steps are conducted in two separate columns.

6. The process of claim 5 wherein said distillation steps are conducted as batch distillations steps.

5 7. The process of claim 5 wherein said distillation steps are conducted as a continuous distillation process.

8. The process of claim 1 wherein said second distillation step is conducted at a pressure of no less than about 50 psia and said first distillation is conducted at a lower pressure.

10

9. The process of claim 8 wherein said first distillation is conducted at a pressure below about 40 psia, and said second distillation is conducted at a pressure of about 50 to about 400 psia.

15 10. The process of claim 9 wherein said first distillation is conducted at a pressure of about 5 to about 30 psia, and said second distillation is conducted at a pressure of about 100 to about 300 psia.

20 11. The process of claim 10 wherein said first distillation is conducted at a pressure of about atmospheric pressure, and said second distillation is conducted at a pressure of about 175 to about 225 psia.

25 12. The process of claim 1, wherein the pressure difference between said first and second distillation is sufficient to result in at least a 10 wt % change in composition of the azeotrope of CFC-12 and HFC-32.

13. The process of claim 12, wherein the pressure difference between said first and second distillation is sufficient to result in at least a 15 wt % change in composition of the azeotrope of CFC-12 and HFC-32.

5 14. The process of claim 1, wherein the yield of HFC-32 is no less than 90%.

10 15. A process for the purification of difluoromethane comprising subjecting an azeotrope of difluoromethane (HFC-32) and dichlorodifluoromethane (CFC-12) to swing distillation such that HFC-32 is recovered with a yield of no less than about 90%.

16. The process of claim 15, wherein the yield is no less than 99%.

15 17. The process of claim 15, wherein said CFC-12 concentration in said azeotrope is no less than about 0.5 wt %.

18. The process of claim 17, wherein said concentration of CFC-12 in said azeotrope is no less than about 9 wt %.

20 19. A process for the purification of difluoromethane comprising:

(a) subjecting a mixture comprising at least difluoromethane (HFC-32) and dichlorodifluoromethane (CFC-12) to a first distillation step in which a majority of either CFC-12 or HFC-32 is concentrated in distillate and a majority of the other component is concentrated in bottoms; and

25

(b) subjecting distillate obtained in a previous distillation step to at least one additional distillation step conducted at a pressure different from the previous distillation step, wherein said additional distillation step causes a majority of the component concentrated in the distillate obtained in the previous distillation step to concentrate in bottoms and causes the other component to concentrate in distillate; and

(c) recovering purified HFC-32 from the bottoms of a distillation step.

20. The process of claim 1, wherein step (b) is repeated one or more times.

1/1




FIG. 1

INTERNATIONAL SEARCH REPORT

In tional Application No

PCT/US 99/05917

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 C07C17/383 C07C19/08 C07C19/10

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 C07C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	WO 94 19301 A (ALLIED SIGNAL INC) 1 September 1994 see the whole document	1-20
Y	WO 97 44301 A (ALLIED SIGNAL INC) 27 November 1997 see claims	1-20

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

15 June 1999

Date of mailing of the international search report

24/06/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Bonnevalle, E

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 99/05917

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 9419301 A		01-09-1994	US 5346595 A	13-09-1994
			EP 0686137 A	13-12-1995
			JP 2800851 B	21-09-1998
			JP 8502758 T	26-03-1996
<hr/>				
WO 9744301 A		27-11-1997	US 5785822 A	28-07-1998
			EP 0912476 A	06-05-1999
<hr/>				